



Product Information:  
**ECOTRANS 75W-80**  
**HEAVY DUTY TRANSMISSION OIL**

### Description

Ecotrans 75W-80 is a synthetic technology, high performance transmission fluid, developed for use in ZF manual and automated manual transmission (AMT) systems. The product not only offers a high level of component protection under a wide range of operating conditions and loads, but improved gear shift and improvements in fuel economy.

### Features and Benefits

- Improved gear shift performance
- Protects components under high load conditions
- Improved transmission efficiency with potential fuel savings
- High temperature stability during sustained long distance schedules

### Applications

Ecotrans 75W-80 can be used in ZF manual and automated manual transmission (AMT) systems fitted to commercial vehicles, light commercial vehicles, coaches and buses, where one of the specifications below is listed. The versatility of Ecotrans 75W-80 allows it to be used in any other types of transmission system requiring an API GL4 lubricant of this viscosity grade.

### Performance Level

API GL- 4  
MAN 341 Type E3, Z-4  
Volvo 97305  
ZF TE ML 01L, 02L, 08, 13\*,16K

Can be used in DAF, Eaton and Iveco transmissions where a product of this type is specified.

\*where ZF TE-ML 13 stipulates ZF TE-ML 02L

### Physical Characteristics

Viscosity @ 100°C, cSt.	9.385
Viscosity @ 40°C, cSt.	55.58
Viscosity Index	152
Flash Point, Closed (°C)	150
Pour Point (°C)	-33

Figures based on average production values.

Part No.s: ECT025, ECT205

(TDS Ecotrans 75W-80 – 020617 Issue 6)

